

SECTION 13 – STREET-LEGAL ALL TERRAIN VEHICLE

An all-terrain vehicle that is a Type I or Type II ATV may now be registered as a Street-legal ATV. These types are defined as:

ATV Type I: 50 inches or less in width, unladen dry weight of 800 lbs or less, having 3 or more low pressure tires, having a seat designed to be straddled, designed and capable to travel over unimproved terrain.

ATV Type II: Any other vehicle not defined as ATV Type I, motorcycle or snowmobile designed for or capable of travel over unimproved terrain. “All-Terrain Type II vehicle” does not include golf carts, any vehicle designed to carry a disabled person, any vehicle not specifically designed for recreation use, or farm tractors

A. Street-legal all-terrain vehicles

1. All-terrain vehicles may be inspected provided that they have been modified to be street legal. They shall be equipped with the following items, which shall comply with the regulations of the department (41-6a-1509).
 - a. One or more headlamps that meet the requirements of U.C.A. 41-6a-1603.
 - b. One or more tail lamps.
 - c. A tail lamp or other lamp constructed and placed to illuminate the registration plate with a white light.
 - d. One or more red reflectors on the rear.
 - e. One or more stop lamps on the rear.
 - f. Amber electric turn signals, one on each side of the front and rear.
 - g. A braking system, other than a parking brake, that meets the requirements of U.C.A. 41-6a-1623.
 - h. A horn or other warning device that meets the requirements of U.C.A. 41-6a-1625.
 - i. A muffler and emission control system that meets the requirements of U.C.A. 41-6a-1626.
 - j. Rearview mirrors on the right and left side of the driver in accordance with U.C.A. 41-6a-1627. **(A Type I ATV requires only a left side mirror and Type II ATV requires both a left side and right side mirror.)**
 - k. A windshield, unless the operator wears eye protection while operating the vehicle.

STREET-LEGAL ALL TERRAIN VEHICLE – Continued

- l. A speedometer, illuminated for nighttime operations.
 - m. Vehicles designed by the manufacturer for carrying one or more passengers, a seat designed for passengers, including a footrest and handhold for each passenger.
 - n. Vehicles with side by side seating, seatbelts for each vehicle occupant.
 - o. Must not be less than 30 inches in width or exceed 70 inches in width. Measurement must be taken at the widest point of the vehicle, including tires.
 - p. Drivers seat must not be less than 30 inches in height or exceed 40 inches in height. This measurement must be made from the ground to the top of the forward edge of the seating position when measured on a flat level surface.
 - q. The tire tread depth must be at least 2/32 of an inch and the tires must not exceed 26 inches in height or be larger than the ATV manufacturer made available for the ATV model.
- 1. **REJECT** when:
 - a) Any of the above requirements are not met.

Note: Sandrails, Rock Crawlers, golf carts and go-carts will not be allowed to be inspected and registered as a street-legal ATV.